

## DATASHEET

---

The small Ambu BlueSensor P features conductive wet gel, offset connector and suitable adhesion to ensure stable signal quality during short term applications. It can be used on children. Thanks to the adhesive, the electrode is gentle to the skin.

### Key benefits

- Offset connector mitigates the impact on signal quality from external forces like pulling of lead wires and pressure on electrodes
- Offset connector allows the user to connect and disconnect the lead wire without applying pressure to the patient or the sensor area, which reduces the risk of gel spreading and adhesive detachment from skin
- Conductive wet gel lowers skin impedance effectively and immediately
- Wet gel optimizes contact between skin and electrode
- Adhesive is gentle to the skin and suitable for short-term application
- Ag/AgCl sensor ensures stable signal quality


# Ambu® BlueSensor P

ECG Electrode

Single use



Wet gel



Foam backing



Silver sensor

**BlueSensor**

**Ambu**

## SPECIFICATIONS

### Dimensions

Electrode size (length x width in mm)	40 x 34
Skin contact size (diameter in mm)	34
Adhesive area (in mm <sup>2</sup> )	754

### Sensor

Sensor material	Silver/silver chloride (Ag/AgCl)
Gel system	Wet gel
Gel area (in mm <sup>2</sup> )	154

### Electrical data (ANSI/AAMI)

AC impedance - typical	650 Ω
DC offset voltage - typical	3.1 mV
Defibrillation overload recovery - typical	11.35 mV
Rate of change of polarization potential - typical	-0.18 mV/s
Combined offset instability and internal noise	8.2 μV
Bias current tolerance (over 8 hours)	6.4 mV

## MATERIALS

### Electrode

Bio-compatible	Yes
Sponge	Polyurethane foam (PUR)
Backing material	Polyvinyl chloride foam (PVC)
Skin adhesive	Acrylate
Upper part	Polyvinyl chloride film (PVC)
Fitting	Polypropylene (PP)
Connector (stud)	Stainless steel
Eyelet	Silver coated plastic
Release liner	Polyethylene film (PE)/Amorphous Polyethylene Terephthalate (APET)

## AVAILABLE CONFIGURATIONS\*

Reference number	Units/liner	Units/pouch	Units/inner box	Units/outer box
P-00-S/10	1	10	1000	2000
P-00-S/12	1	12	960	1920
P-00-A/50	1	50	1000	2000
P-00-F/50	1	50	1000	2000
P-00-S/50	1	50	1000	2000

P-00-S ■ Product ■ Wire length ■ Connector

\*some configurations may not be available worldwide

### Environment

Electrode is not made with natural rubber latex

Packaging is PVC-free

### X-ray & MRI

Radiolucent	No
MR Conditional	No

### Shelf life

Opened pouches	1 month
Unopened pouch*	15 months

\*from date of production

### Packaging

Pouch (outer/middle/inner layers)	Polyester/ Aluminium/ Polyethylene
Boxes	Cardboard

### Options

Non-wired connectors S, A, F

### Precaution

Single use only

## CONNECTORS



S = Stud



A = 4 mm fitting



F = 3 mm fitting

## FEATURES



Printed release liner

# Ambu

Ambu Limited

Incubator 2,  
Alconbury Weald  
Enterprise Campus  
Alconbury Weald  
Cambridgeshire  
PE28 4XA  
United Kingdom  
T +44 1480 498 403  
ambu.co.uk

CE US: Rx only